

Magnetic Vehicle Direction Sensor, Model 4311-MVD



Date Revised: 23 JAN 03

VENDOR DESCRIPTION

The magnetic probes are watertight and airtight. Therefore, they may be installed above ground under a foliage cover, buried underground, or moored under water. Selection of deployment depends upon the amount of cover available in the area under surveillance. The most common placement is underground.



Product Manager
Robotic & Unmanned Sensors

Telephone: (732) 427-5827 / DSN 987

Fax: (732) 427-5072 / DSN 987

e-mail: SFAE-IEWS-NV-RUS@IEWS.monmouth.army.mil

UGS

Power Source		Environmental	
Sensors/Power Transmitters	4 – 6V lantern batteries	High Temp	+60°C/140°F
Supplemental Battery Box	8 – 6V lantern batteries	Low Temp	-30°C/-22°F (Monitor -60°C/-76°F)
Monitor	9 each 1.2V NICAD, 4000mAh 12VDC or 115VAC	Altitude	N/A
Repeater	4 – 6V lantern batteries	Humidity	N/A
		Immersion	N/A
		Sand/Dust	N/A
		Salt	N/A
		Fungus	N/A
		Shock/Vibe	N/A
		EMI/EMC	N/A

Sensor	Description	Detection	Size/Weight	Features
Seismic/Acoustic	Employs sophisticated algorithm to classify targets as personnel, wheeled or tracked veh. based on comb. seismic & acoustic signatures	Tracked Vehicle 0-120 ft Wheeled Vehicle 0-120 ft Personnel 0-30 ft	2.4in x 1.5in x 4.5in Weight: 1.1 lbs	<ul style="list-style-type: none"> ■ Passive detection ■ Covert operation ■ Low false alarm rate ■ Quiescent until activated by targets ■ Operates on lantern batteries ■ Low power DSP
Passive Infrared	Detects temperature differential between target and background. Provides direction and target count.	Tracked Vehicle 0-160 ft Wheeled Vehicle 0-160 ft Personnel 0-80 ft	1.3in x 3.7in or 3.5in x 12.9in Weight: 3.1 lbs.	
Magnetic	Detects movement of ferrous metals. Provides direction and target count.	Tracked Vehicle 0-50 ft Wheeled Vehicle 0-50 ft Personnel 0-8 ft	4in x 3.5in Weight: 1.1lbs	

Device	Description	Message Type	Size/Weight	Features
Monitor	Provides the capability to display sensor transmissions. Can be used to relay sensor data to an external digital display via built-in RS-232 port.	Manchester Format	13in L x 16in W x 7in D Weight: 3.3lbs	<ul style="list-style-type: none"> ■ 2 MHz between channels ■ VHF 162MHz to 174MHz band ■ 2 crystal-controlled frequencies ■ LPI/LPD ultra-short burst transmissions ■ 5-watt transmitters
Repeater	Utilized to overcome line-of-sight obstructions or extend communications range by 50 miles.	Manchester Format	13in L x 12in W x 6in D Weight: 3.3lbs	