

Date Revised: 26 FEB 03

## VENDOR DESCRIPTION

The μCAM<sup>HP</sup> is a highly integrated, fully digital thermal imager. All components are optimized in regard to performance, size and weight.

The key components and performance parameters are:

- Cooled staring CMT array with 384x288 pixels for the 3-5 μm wavelength range with a high thermal resolution of less than 40mK (NETD) for short 1ms integration as required for small UAVs with limited stabilization
- Total power consumption below 18W at all specified ambient temperatures
- Analog and digital video output
- Display options: manual, auto gain/offset with manual correction, histogram mode
- Scene-based nonuniformity correction for good image quality
- Camera control by either RS-232 serial interface or a CAN bus
- Total weight less than 1700 g. Dimensions 220mm x 100mm x 100 mm (L x W x H)
- Wherever light weight or remote operation and control is a key requirement, μCAM<sup>HP</sup> is the optimum value-to-cost camera.



μCAM<sup>HP</sup> IR Sensor System: Observation of Power transfer lines in 4000m distance



**Product Manager**  
**Robotic & Unmanned Sensors**

Telephone: (732) 427-5827 / DSN 987  
Fax: (732) 427-5072 / DSN 987

e-mail: SFAE-IEWS-NV-RUS@iew.s.monmouth.army.mil

EOIR

### Hardware: Infrared Camera Sensor System

Interface: RS-232 or a CAN bus	Optics f=38mm, F/2.5, FOV 14° x 11°
Power: < 18 watts	Range Performance: STANAG 4347, TRM3
Weight: 1.7 kg or 3.74 lbs	Bad Weather Condition: 0.2/km
Dimensions: 220mm x 100mm x 100mm	Identification: 500 m
Detector Type: HgCdTe	Detection: 3000 m
Wavelength range: 3.4 - 5.2 μm	MTBF: 4000 hrs
Pixel: 384 x 288, 24 μm pitch	Environmental Temperature: -40°C to +63°C
Cooling Method: Integral Stirling cooler	
Thermal Resolution: 40 mK at 1 ms	